

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : HIGHDG/AL
Type of product : Aerosol
Vaporizer : Aerosol
Product group : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only
Function or use category : Aerosol

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

U-POL LIMITED
Denington Road
Northants
NN8 2QH Wellingborough - UK
T +44 (0) 1933 230310 - F +44 (0) 1933 425797
technical.department@u-pol.com - www.u-pol.com

1.4. Emergency telephone number

Emergency number : +44 1933 230310 (07:30 - 17:00hrs UK time)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
Liquefied gas H280
Acute Tox. 4 (Dermal) H312
Acute Tox. 4 (Inhalation:gas) H332
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT SE 3 H336

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R20/21

Xi; R36/38

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger
Hazardous ingredients : ethyl methyl ketone, n-butyl acetate
Hazard statements (CLP) : H222 - Extremely flammable aerosol

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

H229 - Pressurised container: May burst if heated
H280 - Contains gas under pressure; may explode if heated
H312+H332 - Harmful in contact with skin or if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (CLP)

: P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing spray, vapours
P264 - Wash hands thoroughly after handling
P280 - Wear eye protection, protective clothing, protective gloves
P312 - Call a doctor if you feel unwell

No labelling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification according to Directive 67/548/EEC |
|--|---|---------|--|
| ethyl methyl ketone | (CAS No) 78-93-3 (EC no) 201-159-0 (EC index no) 606-002-00-3 | 23 - 43 | F; R11 Xi; R36 R66 R67 |
| xylene | (CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 | 5 - 23 | R10 Xn; R20/21 Xi; R38 |
| ethylbenzene | (CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4 | < 5 | F; R11 Xn; R20 |
| 2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit | (CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7 | < 5 | R10 |

| Name | Product identifier | Specific concentration limits |
|--------|---|-------------------------------|
| xylene | (CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 | (C >= 12.5) Xn;R20/21 |

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|---------|--|
| ethyl methyl ketone | (CAS No) 78-93-3 (EC no) 201-159-0 (EC index no) 606-002-00-3 | 23 - 43 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |
| xylene | (CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 | 5 - 23 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 |
| ethylbenzene | (CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4 | < 5 | Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 |
| 2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit | (CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7 | < 5 | Flam. Liq. 3, H226 |

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Get medical advice/attention.

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

| | |
|--------------------------------------|--|
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention. |
| First-aid measures after ingestion | : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|--------------------------------------|--|
| Symptoms/injuries | : May cause genetic defects. |
| Symptoms/injuries after inhalation | : May cause cancer by inhalation. May cause drowsiness or dizziness. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |
| Symptoms/injuries after eye contact | : Causes serious eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|--------------------------------|--|
| Suitable extinguishing media | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream. |

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|--|
| Fire hazard | : Extremely flammable gas. |
| Explosion hazard | : May form flammable/explosive vapour-air mixture. |

5.3. Advice for firefighters

| | |
|--------------------------------|--|
| Firefighting instructions | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|--|
| General measures | : Remove ignition sources. Use special care to avoid static electric charges. Eliminate every possible source of ignition. No open flames. No smoking. |
|------------------|--|

6.1.1. For non-emergency personnel

| | |
|----------------------|--|
| Protective equipment | : Protective clothing. Safety glasses. Gloves. |
| Emergency procedures | : Evacuate unnecessary personnel. |

6.1.2. For emergency responders

| | |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. Avoid breathing spray, vapours. |
| Emergency procedures | : Ventilate area. |

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|--|
| For containment | : Contain leaking substance. Collect spillage. |
| Methods for cleaning up | : Store away from other materials. |

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|---|
| Additional hazards when processed | : Handle empty containers with care because residual vapours are flammable. Flammable gas. |
| Precautions for safe handling | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Avoid breathing spray, vapours. Use only outdoors or in a well-ventilated area. |
| Hygiene measures | : Wash hands thoroughly after handling. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|------------------------|--|
| Technical measures | : Proper grounding procedures to avoid static electricity should be followed. |
| Storage conditions | : Keep only in the original container in a cool, well ventilated place away from : Heat sources, Ignition sources. Keep in fireproof place. Keep container tightly closed. |
| Incompatible products | : Strong bases. Strong acids. |
| Incompatible materials | : Sources of ignition. Direct sunlight. Heat sources. |

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Storage temperature : < 25 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| ethylbenzene (100-41-4) | | |
|--|---------------------------------|-----------------------------------|
| EU | Local name | Ethylbenzene |
| EU | IOELV TWA (mg/m ³) | 442 mg/m ³ |
| EU | IOELV TWA (ppm) | 100 ppm |
| EU | IOELV STEL (mg/m ³) | 884 mg/m ³ |
| EU | IOELV STEL (ppm) | 200 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | Ethylbenzene |
| United Kingdom | WEL TWA (mg/m ³) | 441 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 100 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 552 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 125 ppm |
| United Kingdom | Remark (WEL) | Sk |
| xylene (1330-20-7) | | |
| EU | Local name | Xylene, mixed isomers, pure |
| EU | IOELV TWA (mg/m ³) | 221 mg/m ³ |
| EU | IOELV TWA (ppm) | 50 ppm |
| EU | IOELV STEL (mg/m ³) | 442 mg/m ³ |
| EU | IOELV STEL (ppm) | 100 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | Xylene, o-,m-,p- or mixed isomers |
| United Kingdom | WEL TWA (mg/m ³) | 220 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 50 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 441 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 100 ppm |
| United Kingdom | Remark (WEL) | Sk, BMGV |
| 2-methoxy-1-methylethyl acetate (108-65-6) | | |
| EU | Local name | 2-Methoxy-1-methylethylacetate |
| EU | IOELV TWA (mg/m ³) | 275 mg/m ³ |
| EU | IOELV TWA (ppm) | 50 ppm |
| EU | IOELV STEL (mg/m ³) | 550 mg/m ³ |
| EU | IOELV STEL (ppm) | 100 ppm |
| EU | Notes | Skin |
| United Kingdom | Local name | 1-Methoxypropyl acetate |
| United Kingdom | WEL TWA (mg/m ³) | 274 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 50 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 548 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 100 ppm |
| United Kingdom | Remark (WEL) | Sk |
| ethyl methyl ketone (78-93-3) | | |
| EU | Local name | Butanone |
| EU | IOELV TWA (mg/m ³) | 600 mg/m ³ |
| EU | IOELV TWA (ppm) | 200 ppm |
| EU | IOELV STEL (mg/m ³) | 900 mg/m ³ |
| EU | IOELV STEL (ppm) | 300 ppm |
| United Kingdom | Local name | Butan-2-one |
| United Kingdom | WEL TWA (mg/m ³) | 600 mg/m ³ |
| United Kingdom | WEL TWA (ppm) | 200 ppm |
| United Kingdom | WEL STEL (mg/m ³) | 899 mg/m ³ |
| United Kingdom | WEL STEL (ppm) | 300 ppm |
| United Kingdom | Remark (WEL) | Sk, BMGV |

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

8.2. Exposure controls

| | |
|-----------------------------------|---|
| Personal protective equipment | : Avoid all unnecessary exposure. |
| Materials for protective clothing | : Impermeable clothing |
| Hand protection | : Wear protective gloves |
| Eye protection | : Chemical goggles or safety glasses |
| Skin and body protection | : Wear suitable protective clothing |
| Respiratory protection | : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended |
| Other information | : Do not eat, drink or smoke during use. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | : Gas |
| Appearance | : Aerosol. |
| Colour | : dark grey. |
| Odour | : characteristic. |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Extremely flammable gas |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : insoluble in water. soluble in most organic solvents. |
| Log Pow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

| | |
|-------------|-----------------|
| VOC content | : 619 g/l |
| Gas group | : Liquefied gas |

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable gas.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Dermal: Harmful in contact with skin. Inhalation:gas: Harmful if inhaled.

| | |
|------------------|-----------------------|
| ATE CLP (dermal) | 1100 mg/kg bodyweight |
| ATE CLP (gases) | 4500 ppmv/4h |

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified
Based on available data, the classification criteria are not met
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure) : Not classified
Based on available data, the classification criteria are not met
Aspiration hazard : Not classified
Based on available data, the classification criteria are not met

HIGHDG/AL

| | |
|-----------|---------|
| Vaporizer | Aerosol |
|-----------|---------|

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

HIGHDG/AL

| | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
|-------------------------------|------------------|

12.3. Bioaccumulative potential

HIGHDG/AL

| | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |
|---------------------------|------------------|

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Remove waste in accordance with local and/or national regulations.
Additional information : Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information






In accordance with ADR / RID / IMDG / IATA / ADN

| ADR | IMDG | IATA | ADN | RID |
|--------------------------------------|----------|---------------------|----------|----------|
| 14.1. UN number | | | | |
| 1950 | 1950 | 1950 | 1950 | 1950 |
| 14.2. UN proper shipping name | | | | |
| AEROSOLS | AEROSOLS | Aerosols, flammable | AEROSOLS | AEROSOLS |

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

| ADR | IMDG | IATA | ADN | RID |
|--|---|---|--|---|
| Transport document description | | | | |
| UN 1950 AEROSOLS, 2.1, (D) | UN 1950 AEROSOLS, 2.1 | | | |
| 14.3. Transport hazard class(es) | | | | |
| 2.1 | 2.1 | 2.1 | 2.1 | 2.1 |
|  |  |  |  |  |
| 14.4. Packing group | | | | |
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment : No | Dangerous for the environment : No Marine pollutant : No | Dangerous for the environment : No | Dangerous for the environment : No | Dangerous for the environment : No |

14.6. Special precautions for user

14.6.1. Overland transport

| | |
|---|----------------------|
| Classification code (ADR) | : 5F |
| Special provisions (ADR) | : 190, 327, 344, 625 |
| Limited quantities (ADR) | : 11 |
| Excepted quantities (ADR) | : E0 |
| Packing instructions (ADR) | : P207, LP02 |
| Special packing provisions (ADR) | : PP87, RR6, L2 |
| Mixed packing provisions (ADR) | : MP9 |
| Transport category (ADR) | : 2 |
| Special provisions for carriage - Packages (ADR) | : V14 |
| Special provisions for carriage - Loading, unloading and handling (ADR) | : CV9, CV12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Tunnel restriction code (ADR) | : D |

14.6.2. Transport by sea

| | |
|-----------------------------------|--|
| Special provisions (IMDG) | : 63, 190, 277, 327, 344, 959 |
| Limited quantities (IMDG) | : SP277 |
| Excepted quantities (IMDG) | : E0 |
| Packing instructions (IMDG) | : P207, LP02 |
| Special packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D |
| EmS-No. (Spillage) | : S-U |
| Stowage category (IMDG) | : None |
| Stowage and segregation (IMDG) | : Protected from sources of heat For AEROSOLS with a maximum capacity of 1 litre: Category A. Segregation as for class 9 but 'Separated from' class 1 except division 1.4. For AEROSOLS with a capacity above 1 litre: Category B. Segregation as for the appropriate sub-division of class 2. For WASTE AEROSOLS: Category C. Clear of living quarters. Segregation as for the appropriate sub-division of class 2. |

14.6.3. Air transport

| | |
|--|--------------|
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167 |
| ERG code (IATA) | : 10L |

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

14.6.4. Inland waterway transport

Classification code (ADN) : 5F
Special provisions (ADN) : 19, 327, 344, 625
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E0
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01, VE04
Number of blue cones/lights (ADN) : 1
Carriage prohibited (ADN) : No
Not subject to ADN : No

14.6.5. Rail transport

Classification code (RID) : 5F
Special provisions (RID) : 190, 327, 344, 625
Limited quantities (RID) : 1L
Excepted quantities (RID) : E0
Packing instructions (RID) : P207, LP02
Special packing provisions (RID) : PP87, RR6, L2
Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12
Colis express (express parcels) (RID) : CE2
Hazard identification number (RID) : 23
Carriage prohibited (RID) : No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

VOC content : 619 g/l

Seveso Information : This product is subject to the Seveso Directive

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-phrases:

| | |
|-------------------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |

HIGHDG/AL

Safety Data Sheet

according to Regulation (EC) No. 453/2010

| | |
|-------------------------------|--|
| Acute Tox. 4 (Inhalation:gas) | Acute toxicity (inhalation:gas) Category 4 |
| Aerosol 1 | Aerosol, Category 1 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Liquefied gas | Gases under pressure : Liquefied gas |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 2 | Specific target organ toxicity — Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H222 | Extremely flammable aerosol |
| H225 | Highly flammable liquid and vapour |
| H226 | Flammable liquid and vapour |
| H229 | Pressurised container: May burst if heated |
| H280 | Contains gas under pressure; may explode if heated |
| H304 | May be fatal if swallowed and enters airways |
| H312 | Harmful in contact with skin |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| R10 | Flammable |
| R11 | Highly flammable |
| R20 | Harmful by inhalation |
| R20/21 | Harmful by inhalation and in contact with skin |
| R36 | Irritating to eyes |
| R36/38 | Irritating to eyes and skin |
| R38 | Irritating to skin |
| R66 | Repeated exposure may cause skin dryness or cracking |
| R67 | Vapours may cause drowsiness and dizziness |
| F | Highly flammable |
| Xi | Irritant |
| Xn | Harmful |

UPOL SDS EU (no product code)

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyer's responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.